






Tile with the modular size of 600 x 600 mm is produced with edge A, B, D2 og E.

Surface :	Gyptone Quattro 22 is supplied pre-painted white NCS 0500, in design with edge A, D2 and E15, all with a gloss value of 5-9. Quattro 22 with edge B is supplied unpainted.
Design:	Gyptone Quattro 22 is based on a 12,5 mm thick Gyproc plasterboard for edge D2 and B. For the edge A and E, the board is 10 mm thick. Perforated area: 9 % The tile is perforated with quattro pattern 9 x 9 mm, cc19,5 mm.    
Technic:	Gyptone products with edge B og D2 is produced according to the drawing. Gyptone products with edge A is produced 6 mm and edge E 8mm shorter than the standard module, in length and width. The weight is approximately 8 kg/m ² for 12,5 mm and 7 kg/m ² for 10 mm board.

Perforation

GYPTONE QUATTRO 22

 <p>GYPROC A/S HARESKOVVEJ 12 4400 KALUNDBORG TLF. + 45 59 57 03 30 FAX. +45 59 57 03 01</p>	<p>Drawn by JFP</p>	<p>Date 03.08.2007</p>	<p>Drawing No. Q22</p>
	<p>Measure 1:10</p>	<p>REV. DATO: 22.04.2015</p>	